

DUO

BALLISTIC INSPIRATION

Inspired by X1000 goggle, from the Tactical range, the goggle DUO offers a total and reinforced protection thanks to its double lens and its Equalizer technology.



DUODEPSI



100 g

- + PANORAMIC FIELD OF VISION**
- + TPR FRAME**
- + ANTI-SCRATCH , ANTI-FOG COATINGS**
- + EQUALIZER TECHNOLOGY**

- + NEOPRENE STRAP: BETTER RESISTANCE TO HYDROCARBONS (OIL, GAS, ...) AND WATER.**

bolle
SAFETY

DUO

BALLISTIC INSPIRATION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
DUO	Sealed double screen EQUALIZER	DUODEPSI	2C-1,2  1 BT 	 EN166 3 4 BT 	Anti-scratch/Anti fog

LENS MARKING

Optical class symbols:



1. Continuous work

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

 European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.

4. Large dust particles > 5 microns.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

 European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

EQUALIZER

Equalizer is the high performance goggle system for protecting against fog. thanks to its double lens and regulation patch, the equalizer filters and regulates moisture levels in the goggles.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN 13 CODE	
	DUODEPSI
Individual plastic bag	3660740006907
Box of 5 safety goggles	3660740106904
120 safety goggle per outer pack	3660740206901

CHARACTERISTICS	
LENSES	PC - 2,85 mm - Curve 4,9
FRAME	TPR
TEMPLES	Non applicable
STRAP	Neoprene
FOAM	Yes



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle-safety.com

bolle
SAFETY